

# ICONIC

touch the design



**LIGHT  
IT  
UP!**

# Company About

It all started with a passion for light. EVORINO lighting was born in 2016 with its experience and knowledge. We are working to develop luminaires of high quality and standards that direct the light with their style and aesthetics. With its structure that produces solutions for projects, we direct the products with lighting designers, architects and planners. We produce exciting products with a structure that pushes the limits of technique and design, and we bring these products together with the whole world.

We are constantly expanding our current product portfolio that can be adapted to the needs of our customers. Our knowledge, understanding of quality, experienced staff, equipment and machinery have brought us success. We have continued and continue to work with the source of satisfaction by serving each of our customers in their next projects.

Over the years Evorino has built its growth based on in-house design, R&D, quality control, testing and production. From design to engineering and prototyping, production, packaging and stocking, everything is handled at the Evorino headquarters in Turkey.

## Technology & LED


We have been experiencing LED technology since its debut. It's probably the biggest advancement in lighting technology in decades. EVORINO plays a good role in applying this technology, designing and manufacturing its own LED boards, developing innovative LED products and custom solutions, enabling designers and users to make the most of previously unimagined possibilities in lighting.

The true measure of cost goes beyond just the initial purchase cost, but also includes intelligent lighting control, lifetime, maintainability and operating costs. Combining extensive product knowledge with a wide range of energy efficient product solutions and industry-specific experience, EVORINO guides you through an environmentally friendly, cost-effective and sustainable selection process without sacrificing light quality.



# Design

Our people research and anticipate trends and develop concepts at the cutting edge of lighting technology. We work with international lighting designers, architects and planners who are constantly trying to explore boundaries and enable challenging designs. Courage and openness are the values of our Design Lab that generate groundbreaking innovations.



# Project

Due to the enormous energy reduction, minimal heat output, low maintenance and long lifetime, LEDs are proven to provide the best return on investment. EVORINO's luminaires were developed to set standards in watts consumed per square metre, and the company's extensive manufacturing capabilities allow focus on a high price/quality ratio. EVORINO's expert team is ready to assist you in calculating ROI for your projects.



# Customized Solutions

Even the most comprehensive product portfolio cannot always meet the specific requirements of a design. That's why we work with you to develop bespoke lighting solutions that are precisely tailored to the architectural and aesthetic needs of your project. Depending on the size of the project, we implement both small adaptations to existing EVORINO products and designs for completely new innovations.



# Production

We are confident that the highest quality and flexibility can only be achieved with in-house expertise throughout the value chain. We produce completely in-house. From electronics manufacturing, turning, milling, laser engraving and die casting to final painting and finishing, every step is carried out in our modern production facilities. This gives us maximum quality control, even for one-off and bespoke products, and allows us to react agile to customer requirements. And we pay attention to our environment.

We are stronger with mold technology. Every day a new one is added to our molds, this allows us to design and produce extraordinary products.

Products take shape in our Injection Printing facility. Injection allows us to obtain fast and high quality finishes. This provides us with standardization and the ability to produce fast products.

The final touch of paint production, the texture of the paint is very important to us. Finishes make the texture of the products more enjoyable, we offer our customers countless combination product options by applying thousands of color alternatives to our standard products with unlimited color alternatives in our paint facility.





# Quality & Warranty

We manufacture our products with care, All employees receive extensive training to guarantee the best standards of workmanship.

Throughout the entire production process, EVORINO differentiates itself by addressing the strictest quality parameters to ensure that products and services are designed and manufactured to exceed customer requirements. Every step in the manufacturing process has a routine quality procedure that covers both product quality and testing. That's why every product leaving EVORINO is thoroughly examined and tested, ensuring minimum returns and maximum efficiency.

We trust our products. Guaranteed EVORINO luminaires are manufactured to meet the highest standards. Today, tomorrow and five years from now. You can also benefit from our 5-year warranty, as we are sure of the quality of the materials we use, thanks to the production processes, sustainable technologies developed with the latest technology.



# Sustainability

EVORINO invests in and continues to pursue a green-oriented philosophy for all company departments, from offices to production and warehouse. For many years, the company has devoted itself to limiting the environmental impact of its various operations as well as allocating resources, thanks to measures that support sustainable development, such as the use of renewable energies, which are almost entirely self-produced, and the reduction of consumption and CO2 emissions. recovery and recycling of production scraps and raw materials. These are just a few of the eco-friendly operations undertaken to develop a virtuous economic model. It goes without saying that all our areas in our factory are illuminated with energy-efficient LEDs.

Our production and logistics processes are constantly optimized to reduce the impact on the environment as much as possible. That's why our shipping packaging is made from recyclable material to minimize the shipping volume and amount of padding.

As a company, we see ourselves as part of a larger whole that we are connected to now and for a future worth living. Not only because our products can make a significant contribution to improving the climate balance of our customers, but also for the use of sustainable energy sources, for example, or conscious Group strategies for climate-business travel and mobility management. Social responsibility is as important to us as ecological responsibility, which is why we have identified sustainability as the core principle of our actions at all organizational levels.

We believe that the lifecycle of our actions and products should be traceable and transparent, which requires a move to clear standards. Accordingly, in addition to ISO9001,




# Logistics

We are always with you. We are eager to work with lighting planners, architects and designers all over the world. International change and shared passion for light shaped the character of EVORINO. We develop, manufacture and deliver innovative luminaires to our customers worldwide.



## Recessed / Spotlight



ICONIC-R-Q4  
10



ICONIC-R-L4  
12

## Semi Recessed / Spotlight



ICONIC-SR-Q4  
14



ICONIC SLIM-SR-Q4-ADJ  
16



ICONIC-SR-L4-ADJ-H  
18



ICONIC-SR-L4-ADJ-V  
19

## Surface Mounted / Spotlight



ICONIC-N-Q4  
20




ICONIC-N-L4  
22



ICONIC SLIM-N-Q4-ADJ  
23



ICONIC-N-Q4-IP  
24



ICONIC-N-L4-ADJ-H  
26



ICONIC-N-L4-ADJ-V  
27

## Track Mounted / Tracklight



ICONIC-T-Q4  
28



ICONIC SLIM-T-Q4  
29



## Wall Mounted / Spotlight



ICONIC-W-Q4  
32



ICONIC-W-Q4-IP  
33



ICONIC-W-Q4-AS  
34

## Open Cell (Grid) Ceiling





ICONIC-C-Q4  
36

## Baffle Ceiling




ICONIC-B-Q4  
38

# ICONIC-R-Q4



**Product Family Code**  
E1.2.3.1.0025



## Product Features

Mounting Location	Ceiling
Mounting Type	Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP44 (Front) / IP20 (Back)
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Dimension

Width	100 mm
Length	100 mm
Height	75 mm
Cut-Out	90 mm x 90 mm
Min. Recessed Depth	75 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	II
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)



## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:100 mm X B:100 mm X H:75 mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT



# ICONIC-R-L4



**Product Family Code**  
E1.2.3.1.0122



## Product Features

Mounting Location	Ceiling
Mounting Type	Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP44 (Front) / IP20 (Back)
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Dimension

Width	60 mm
Length	180 mm
Height	65 mm
Cut-Out	50 mm X 170 mm
Min. Recessed Depth	65 mm


## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	II
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)


## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:60mm X B:180mm X H:65mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT



# ICONIC-SR-Q4



**Product Family Code**  
E1.5.3.1.0217



## Product Features

Mounting Location	Ceiling
Mounting Type	Semi Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Dimension

Width	105 mm
Length	105 mm
Height	100 mm
Cut-Out	Ø90 mm
Min. Recessed Depth	60 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	II
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)


## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19


A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT



# ICONIC SLIM-SR-Q4-ADJ



**Product Family Code**  
E1.5.3.1.0219



## Product Features

Mounting Location	Ceiling
Mounting Type	Semi Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Dimension

Width	105 mm
Length	105 mm
Height	70 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:70mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT







# DESING

Its simple design and its square shape let you use ICONIC throughout the project, as it blends in perfectly in any architectural environment, combining clean cut optical performance, light quality and visual comfort.

# ICONIC-SR-L4-ADJ-H



**Product Family Code**  
E1.5.3.1.0205



## Product Features

Mounting Location	Ceiling
Mounting Type	Semi Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	II
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

## Dimension


Width	50 mm
Length	170 mm
Height	52 mm
Cut-Out	Ø86
Min. Recessed Depth	50 mm

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:50mm X B:170mm X H:52mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT

# ICONIC-SR-L4-ADJ-V



**Product Family Code**  
E1.5.3.1.0206



## Product Features

Mounting Location	Ceiling
Mounting Type	Semi Recessed
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	II
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

## Dimension

Width	50 mm
Length	170 mm
Height	52 mm
Cut-Out	Ø86
Min. Recessed Depth	50 mm

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:50mm X B:170mm X H:52mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT

# ICONIC-N-Q4



## Product Family Code E1.1.3.1.0061



### Product Features

Mounting Location	Ceiling
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

### Light Output

Adjustability	Fixed
Light Distribution	Direct

### Dimension

Width	105 mm
Length	105 mm
Height	100 mm

### Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)


### Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT



# ICONIC-N-L4



## Product Family Code E1.1.3.1.0209



### Product Features

Mounting Location	Ceiling
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

### Light Output

Adjustability	Fixed
Light Distribution	Direct

### Dimension

Width	60 mm
Length	180 mm
Height	100 mm

### Electrical Data


Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

### Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:60mm X B:180mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC SLIM-N-Q4-ADJ



**Product Family Code**  
E1.1.3.1.0220



## Product Features

Mounting Location	Ceiling / Wall
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Dimension

Width	105 mm
Length	105 mm
Height	70 mm

## Electrical Data


Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:70mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC-N-Q4-IP



## Product Family Code E2.1.3.1.0210



### Product Features

Mounting Location	Ceiling
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP65
Origin	Turkey
Warranty	Up to 5 Years

### Light Output

Adjustability	Fixed
Light Distribution	Direct

### Dimension

Width	105 mm
Length	105 mm
Height	120 mm

### Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

### Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:120mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT






# ICONIC-N-L4-ADJ-H



**Product Family Code**  
E1.1.3.1.0207



## Product Features

Mounting Location	Ceiling / Wall
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

## Dimension


Width	50 mm
Length	170 mm
Height	52 mm

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:50mm X B:170mm X H:52mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC-N-L4-ADJ-V



**Product Family Code**  
E1.1.3.1.0208



## Product Features

Mounting Location	Ceiling / Wall
Mounting Type	Surface Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Dimension

Width	50 mm
Length	170 mm
Height	52 mm

## Electrical Data


Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:50mm X B:170mm X H:52mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC-T-Q4



**Product Family Code**  
E1.4.4.1.0060



## Product Features

Mounting Location	Ceiling
Mounting Type	Track Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Dimension

Width	105 mm
Length	105 mm
Height	100 mm

## Electrical Data


Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Performance Data


Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105 mm X B:105 mm X H: 100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC SLIM-T-Q4



**Product Family Code**  
E1.4.4.1.0218



## Product Features

Mounting Location	Ceiling
Mounting Type	Track Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Adjustable
Light Distribution	Direct
Tilt Angle	-90° / +90°

## Dimension

Width	105 mm
Length	105 mm
Height	70 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung
Dimming	Optional (Depends On Driver)

## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:70mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT



# Family Overview

## **ENDLESS POSSIBILITIES**

Within the same design language, ICONIC offers multiple power outputs in different sizes and with various dimming possibilities, a range of optics and a set of accessories to enhance the visual wellbeing. Which one to use? The choice is up to you!




UGR < 19

**UNIFIED GLARE RATING**

Provides eye comfort through its low glare rating

# ICONIC-W-Q4



## Product Family Code E1.7.5.1.0140



### Product Features

Mounting Location	Wall
Mounting Type	Wall Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

### Light Output

Adjustability	Fixed
Light Distribution	Direct

### Dimension

Width	105 mm
Length	105 mm
Height	100 mm

### Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)



### Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT



# ICONIC-W-Q4-IP



**Product Family Code**  
E2.7.5.1.0139



## Product Features

Mounting Location	Wall
Mounting Type	Wall Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP65
Origin	Turkey
Warranty	Up to 5 Years

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Performance Data



Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

## Dimension

Width	105 mm
Lenght	105 mm
Height	100 mm

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT

# ICONIC-W-Q4-AS



**Product Family Code**  
E1.7.5.1.0098



## Product Features

Mounting Location	Wall
Mounting Type	Wall Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Dimension

Width	100 mm
Length	130 mm
Height	275 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)



## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:100 mm X B:130 mm X H:275 mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT



# ICONIC-C-Q4



**Product Family Code**  
E1.9.3.1.0216



## Product Features

Mounting Location	Ceiling
Mounting Type	Open Cell
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Dimension

Width	117 mm
Length	117 mm
Height	75 mm
Grid	100 mm x 100 mm
Min. Recessed Depth	75 mm

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Excluded)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)


## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:117 mm X B:117 mm X H:75 mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	1 1 Hours 3 3 Hours 9 W/O KIT



# ICONIC-B-Q4



**Product Family Code**  
E1.10.3.1.0102



## Product Features

Mounting Location	Ceiling
Mounting Type	Buffle Ceiling Mounted
Light Source	SMD LED
Optic	Lens + Dark Reflector
Body Material	Aluminum
Body Paint	Acrylic
IP Rating	IP20
Origin	Turkey
Warranty	Up to 5 Years

## Electrical Data

Operating Voltage	220V - 240V AC
Operating Frequency	50 Hz / 60 Hz
Electrical Protection Class	I
Driver (Included)	Osram
Led	Samsung / Cree
Dimming	Optional (Depends On Driver)

## Light Output

Adjustability	Fixed
Light Distribution	Direct

## Performance Data

Operating Temperature (ta)	-20°C to +45°C
Storage Temperature	-30°C to +60°C
Colour rendering index (CRI)	Ra>80 / Ra>90
Rated life (L70)	60 000 h
System Efficiency (lm/W)	Up to 115
UGR Rate	<19












































## Dimension

Width	105 mm
Lenght	105 mm
Height	100 mm

A   LIGHT SOURCE	B   DIMENSIONS	C   LIGHT COLOR	D   POWER	E   CONTROL	F   BODY COLOR	G   BODY FINISH	H   OPTIC	I   EMERGENCY KIT
1 LED	1 A:105mm X B:105mm X H:100mm	1 2700K Ra>80 2 3000K Ra>80 3 4000K Ra>80 4 6500K Ra>80 5 2700K Ra>90 6 3000K Ra>90 7 4000K Ra>90 8 6500K Ra>90	6 6 Watt 8 8 Watt 10 10 Watt 12 12 Watt 14 14 Watt 20 20 Watt 24 24 Watt 28 28 Watt	1 ON-OFF 2 DALI 3 PHASE-CUT	1 RAL9003 2 RAL9016 3 RAL9010 4 RAL9006 5 RAL7011 6 RAL7016 7 RAL7021 8 RAL9004 9 RAL9005 99 OTHER	1 Matt 2 Texture	50 50° 80 80°	9 W/O KIT



## how to read symbols & suffixes

	Led Light		Protection class III, Safety Extra-Low Voltage (SELV)
	Ceiling - Recessed Mounting		Motion sensor
	Ceiling - Suspended Mounting		The luminaire can be rotated around the value of the number
	Ceiling - Surface Mounting		The luminaire is around the value of the number uniaxial tilttable
	Wall - Wall Surface Mounted		The luminaire is around the value of the number uniaxial tilttable
	Wall - Wall Recessed Mounting		The luminaire is cardan tilttable around the value of the number
	Floor - Free Standing		The light is one-sided around the value of the number tilttable
	Floor - Fixed Standing		Fixed
	Floor - Surface Mounting		Mains voltage and frequency
	Floor - Recessed Mounting		Operating Voltage
	Ceiling - Cell Ceiling		Installation without tools
	Ceiling - Semi Recessed		Energy efficiency
	Ceiling - Direct and Indirect		Product with TSE mark
	Ceiling - Track Mounted		VDE certified (Association of German Elect. Engineers)
	Ceiling - Baffle Ceiling		CE certified
	Degree of protection against solid bodies and penetration by liquids		Product with ENEC mark
	Protection classes (Back) Protection classes (Front)		Product with RoHS mark
	Driver excluded		Disposing of luminaires
	Driver included		
	Led luminaire must not be covered by any materials		
	Level of shock resistance		
	Square wall or ceiling cut-out		
	Round wall or ceiling cut-out		
	Protection class I, protection insulation		
	Protection class II, protection insulation		



## Protection Classes

---

### IPXY

#### 1st (x) digit: foreign body protection

IP 1X protection against penetration of foreign bodies  $\geq$  50mm  
IP 2X protection against penetration of foreign bodies  $\geq$  12mm  
IP 3X protection against penetration of foreign bodies  $\geq$  2.5mm  
IP 4X protection against penetration of foreign bodies  $\geq$  1mm  
IP 5X protection against harmful dust deposit  
IP 6X protection against dust entry

#### 2st (y) digit: water protection

IP 1X protection against drops water falling vertically  
IP 2X protection against drops water from angles up to 15°  
IP 3X protection against showers up to 60°  
IP 4X protection against splash water  
IP 5X protection against temporary immersion  
IP 6X protection against permanent submersion

### IKxx


Resistance to external mechanical impacts: IK code refers to the maximum external impact the luminaire is capable to withstand, without irreversible damage. In compliance with EN50102 standards. recessed wall and ceiling installation, suspended fitting.

IK code	Impact Energy	Mass/Height
IK00	0,00 Joule	-
IK01	0,15 Joule	0,2Kg/70mm
IK02	0,20 Joule	0,2Kg/100mm
IK03	0,35 Joule	0,2Kg/175mm
IK04	0,50 Joule	0,2Kg/250mm
IK05	0,70 Joule	0,2Kg/250mm
IK06	1,00 Joule	0,5Kg/200mm
IK07	2,00 Joule	0,5Kg/400mm
IK08	5,00 Joule	1,7Kg/295mm
IK09	10,00 Joule	5,0Kg/200mm
IK10	20,00 Joule	5,0Kg/400mm

## Mounting Type

---

-R	Recessed
-N	Surface Mounted
-S	Suspended
-SR	Semi Recessed
-T	Track mounted
-W	Wall Mounted
-WR	Wall Recessed
-C	Cell Ceiling
-B	Buffle Ceiling
-AS	Asymmetric
-TR	Trimless





Evorino

[evorino.com](http://evorino.com)